



TREE 8TX metal GE - Unmanaged Gigabit Switch - 8 ports

Art.No.: 58173  
Weight: 0.542 kg  
Country of origin: TW  
Model designation: TREE 8 TX Metal GE

8 port Gigabit unmanaged Switch  
Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Header	
Material short text	TREE 8 TX Metal GE
Commercial data	
URL Webshop	<a href="https://shop.murrelektronik.com/58173">https://shop.murrelektronik.com/58173</a>
GTIN	4048879735582
ECLASS-6.0	19170106
ECLASS-6.1	19170106

ECLASS-7.0	19170106
ECLASS-7.1	19170106
ECLASS-8.0	19170106
ECLASS-8.1	19170106
ECLASS-9.0	19170402
ECLASS-9.1	19170106
ECLASS-10.0.1	19170402
ECLASS-10.1	19170402
ECLASS-11.0	19170402
ECLASS-11.1	19170402
ECLASS-12.0	19170402
ECLASS-13.0	19170402
ECLASS-14.0	19170402
ETIM-5.0	EC000734
ETIM-6.0	EC000734
ETIM-7.0	EC000734
ETIM-8.0	EC000734
customs tariff number	85176200
EAN	4048879735582
Packaging unit	1
customs tariff number	85176200
EAN	4048879735582
Packaging unit	1

**Electrical data | Supply**

Operating voltage DC min.	9 V
Operating voltage DC max.	48 V
Current consumption max.	450 mA

**Industrial Communication**

Data transmission rate max.	1.000 Mbit/s
-----------------------------	--------------

**Industrial communication | Ethernet functionality**

VLAN unmanaged (IEEE 802.1Q)	Yes
Switch type	unmanaged
duplex	Full duplex
Auto-negotiation	Yes
Auto-crossover	Yes

**Diagnostics**

Alarm contact	No
Diagnostic	No voltage
LED display	Ethernet connection/data traffic

**Device protection | Electrical**

Degree of protection (EN IEC 60529)	IP40
Invers-polarity protection	Yes
Over voltage protection	Yes

**Mechanical data | Material data**

Material housing	Metal
Color housing	black

**Mechanical data | Mounting data**

Height	90 mm
Width	45,2 mm
Depth	78,7 mm
Mounting method	geschnappt

Suitable for mounting type

Mounting rail TH35, (EN 60715)

**Environmental characteristics | Climatic**

Operating temperature min.	-10 °C
Operating temperature max.	70 °C
Ambient temperature (storage, transport)	-40 °C

**Connection type 2**

Connection type 1	8
Connection type 2	X1
Family construction form	RJ45
No. of poles	8
Gender	female
Color contact carrier	black
PIN 1	TD +
PIN 2	TD -
PIN 3	RD +
PIN 4	n.c.
PIN 5	n.c.
PIN 6	RD -
PIN 7	n.c.
PIN 8	n.c.
Family construction form	terminal
No. of poles	5
Gender	male
Color contact carrier	green
Connection	Plug-in terminals RK
PIN 1	24 V DC (UB 2)
PIN 2	0 V
PIN 3	24 V DC (UB 1)
PIN 4	0 V
PIN 5	PE