

**MODLINK MSDD SINGLE COMBI INSERT USA NEMA 1-15**

1xSUD-D25 female/male + 1xRJ45 female/female

1 × NEMA 1-15 (plug-solder connection)

1 × RJ45, 8-pole metal, CAT5e (female/female)

1 × SUB-D25 (female/male)

[Link to Product](#)**Illustration**

Product may differ from Image

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27189217      |
| ECLASS-6.1            | 27189217      |
| ECLASS-7.0            | 27189217      |
| ECLASS-8.0            | 27189217      |
| ECLASS-9.0            | 27182806      |
| ECLASS-10.1           | 27182806      |
| ECLASS-11.1           | 27182806      |
| ECLASS-12.0           | 27182806      |
| ETIM-5.0              | EC000020      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879037242 |
| Packaging unit        | 1             |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 30 mm |

**Environmental characteristics | Climatic**

|                          |       |
|--------------------------|-------|
| Storage temperature min. | 5 °C  |
| Storage temperature max. | 40 °C |

**USA**

|                     |              |
|---------------------|--------------|
| Connection geometry | 4.8 x 0.5 mm |
|---------------------|--------------|

|                            |                        |
|----------------------------|------------------------|
| Operating voltage AC       | 125 V                  |
| Operating current          | 15 A                   |
| Connection                 | Plug-solder connection |
| No. of poles               | 2 + PE                 |
| Protection contact present | yes                    |

**SUB-D25**

|                                       |  |
|---------------------------------------|--|
| Operating voltage AC                  | 48 V   |
| Operating voltage DC                  | 48 V   |
| Operating voltage AC max. (UL-listed) | 30 V   |
| Operating voltage DC max. (UL-listed) | 42,4 V   |
| Operating current                     | 3 A  |
| Current operating max. (UL)           | 175 mA   |
| Family construction form              | SUB-D25  |
| Family type Back side                 | SUB-D25  |
| Gender                                | female   |
| Gender Rear                           | male   |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 25   |

**RJ45**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |