

MODLINK MSDD DBL COMBI INSERT USA 2XNEMA 5-15

GFCI+2xRJ45 female/female + 1x3A fuse

Art.No.: 4000-68000-4120000
Weight: 0.261
Country of origin: CN
Model designation: Fr.Modul-AB-125-15-GFCI-SC+2xRJ45+fuse3A

2× NEMA-GFCI 5-15 (screw terminals)
2× RJ45, 8-pole metal, CAT5e (female/female)
1× fuse (3 A)
with touch protection

Link to Product

Illustration



Product may differ from Image



| Header | |
|---------------------|--|
| Material short text | Fr.Modul-AB-125-15-GFCI-SC+2xRJ45+fuse3A |
| Commercial data | |
| URL Webshop | https://shop.murrelektronik.com/4000-68000-4120000 |
| GTIN | 4048879369275 |
| ECLASS-6.0 | 27189217 |
| ECLASS-6.1 | 27189217 |
| ECLASS-7.0 | 27189217 |
| ECLASS-7.1 | 27189217 |
| ECLASS-8.0 | 27189217 |
| ECLASS-8.1 | 27189217 |
| ECLASS-9.0 | 27182806 |
| ECLASS-9.1 | 27189217 |
| ECLASS-10.0.1 | 27182806 |
| ECLASS-10.1 | 27182806 |
| ECLASS-11.0 | 27182806 |
| ECLASS-11.1 | 27182806 |
| ECLASS-12.0 | 27182806 |

| | |
|-----------------------|---------------|
| ECLASS-13.0 | 27182806 |
| ECLASS-14.0 | 27182806 |
| ETIM-5.0 | EC000020 |
| ETIM-6.0 | EC000020 |
| ETIM-7.0 | EC000020 |
| ETIM-8.0 | EC000020 |
| customs tariff number | 85366990 |
| EAN | 4048879369275 |
| Packaging unit | 1 |

Mechanical data | Mounting data

| | |
|--------|--------|
| Height | 88 mm |
| Width | 116 mm |
| Depth | 72 mm |

Environmental characteristics | Climatic

| | |
|--------------------------|--------|
| Storage temperature min. | -40 °C |
| Storage temperature max. | 70 °C |

Fuse

| | |
|----------------------|-------|
| Operating voltage AC | 250 V |
| Operating voltage DC | 32 V |
| Nominal current | 3 A |

USA

| | |
|-------------------------------|--------------------|
| Connection | Screw terminals SK |
| No. of poles | PE |
| Connections per pole | 2 |
| Protection contact present | yes |
| Connection cross section max. | 6 mm ² |
| AWG number max. | 10 |
| Operating voltage AC | 125 V |
| Operating current | 15 A |

RJ45

| | |
|---------------------------------------|-------------------|
| Family construction form | RJ45 |
| Looking techniques | Snap-in connector |
| Cable category min. | Cat5e |
| Family type Back side | RJ45 |
| Operating voltage AC max. (UL-listed) | 30 V |
| Operating voltage DC max. (UL-listed) | 42.4 V |
| Current operating max. (UL) | 175 mA |