

Signal tower Modlight70 Pro equipped with LED modules

green,amber,red,buzzer,M12 plug downward

Art.No.: 4000-76705-5310000

Weight: 0.47

Country of origin: CZ

Model designation: Modlight70 Pro BASE M12-8U LED-GYR BUZ.


Basic, buzzer, flash + LED modules + M12 (down)

green, yellow, red

Link to Product

Illustration





Product may differ from Image





Header	
Material short text	Modlight70 Pro BASE M12-8U LED-GYR BUZ.
Commercial data	
URL Webshop	https://shop.murrelektronik.com/4000-76705-5310000
GTIN	4048879759939
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-7.1	27371230
ECLASS-8.0	27371230
ECLASS-8.1	27371230
ECLASS-9.0	27371230
ECLASS-9.1	27371230
ECLASS-10.0.1	27371230
ECLASS-10.1	27371230
ECLASS-11.0	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ECLASS-13.0	27371230
ECLASS-14.0	27371230



stay connected

ETIM-5.0	EC001042
ETIM-6.0	EC001042
ETIM-7.0	EC001042
ETIM-8.0	EC001042
customs tariff number	85318070
EAN	4048879759939
Packaging unit	1
Electrical data Supply	
Operating voltage DC	24 V
Operating voltage DC min.	21.6 V
Operating voltage DC max.	26.4 V
Current consumption max.	385 mA
НМІ	
Buzzer sound	fast beep, continuous beep, fast high-low, sweep tone
Sound pressure at 1 m	90 dB
Reduced sound pressure at 1 m	80 dB
HMI Illumination properties	
Blink cycles	60 ±12 per minute
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	locked, inserted
Mechanical data Material data	
Material housing	Plastic
Color housing	black
Mechanical data Mounting data	
Height	293 mm
Width	70 mm
Depth	70 mm
Environmental characteristics Climatic	
Operating temperature min.	-30 °C
Operating temperature max.	60 °C