

Signal tower Modlight70 Pro equipped with LED modules

green,amber,red,buzzer,M12 plug side

Art.No.: 4000-76713-5310000  
Weight: 0.475  
Country of origin: CZ  
Model designation: Modlight70 Pro BASE M12-8S LED-GYR BUZ.


Basic, buzzer, flash + LED modules + M12 (side)  
green, yellow, red

Link to Product

Illustration



Product may differ from Image



Commercial data

URL Webshop	<a href="https://shop.murrelektronik.com/4000-76713-5310000">https://shop.murrelektronik.com/4000-76713-5310000</a>
GTIN	4048879759953
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-7.1	27371230
ECLASS-8.0	27371230
ECLASS-8.1	27371230
ECLASS-9.0	27371230
ECLASS-9.1	27371230
ECLASS-10.0.1	27371230
ECLASS-10.1	27371230
ECLASS-11.0	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ECLASS-13.0	27371230
ECLASS-14.0	27371230
ETIM-5.0	EC001042
ETIM-6.0	EC001042

ETIM-7.0	EC001042
ETIM-8.0	EC001042
EAN	4048879759953

**Electrical data | Supply**

Operating voltage DC	24 V
Operating voltage DC min.	21.6 V
Operating voltage DC max.	26.4 V
Current consumption max.	385 mA

**HMI**

Buzzer sound	fast beep, continuous beep, fast high-low, sweep tone
Sound pressure at 1 m	90 dB
Reduced sound pressure at 1 m	80 dB

**HMI | Illumination properties**

Blink cycles	60 ±12 per minute
--------------	-------------------

**Device protection | Electrical**

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	locked, inserted

**Mechanical data | Material data**

Material housing	Plastic
Color housing	black

**Mechanical data | Mounting data**

Height	293 mm
Width	70 mm
Depth	70 mm

**Environmental characteristics | Climatic**

Operating temperature min.	-30 °C
Operating temperature max.	60 °C